

Cable Assemblies

Low PIM RF Coax

1/4 inch Super Flexible Times Microwave SPO-250™ Cable

Low Loss, Low PIM Coaxial Cables

- IM3 4.3-10 (only): $\leq -160\text{dBc}@700\text{MHz} \& 1900\text{MHz}$
IM3 (all others): $\leq -155\text{dBc}@700\text{MHz} \& 1900\text{MHz}$
- Corrugated copper outer conductor providing greater than 100dB shielding
- Cable assemblies are 100% PIM tested
- Super flexible for ease of installation
- Durable black polyethylene outer jacket suitable for outdoor use

Custom Lengths Available
XX = custom length in inches
 Contact sales about custom lengths

Cable Images for illustration purposes



4.1-9.5 (Mini) DIN Male

4.3-10 Male

7-16 DIN Male

7-16 DIN Male Right Angle

N Female

N Male

QMA Male

| Part Number and Cable Length | | Connector End | |
|------------------------------|----------------------|---------------------------|---------------------------|
| 39 inches (1 meter) | 78 inches (2 meters) | Connector 1 | Connector 2 |
| P2RFC-2316-39 | P2RFC-2316-78 | 4.1-9.5 (Mini) DIN Male | 4.1-9.5 (Mini) DIN Male |
| P2RFC-2376-39 | P2RFC-2376-78 | 4.1-9.5 (Mini) DIN Male | N Female |
| P2RFC-2370-39 | P2RFC-2370-78 | 4.3-10 Male | 4.3-10 Male |
| P2RFC-2372-39 | P2RFC-2372-78 | 4.3-10 Male | 4.1-9.5 (Mini) DIN Male |
| P2RFC-2373-39 | P2RFC-2373-78 | 4.3-10 Male | N Female |
| P2RFC-2374-39 | P2RFC-2374-78 | 4.3-10 Male | N Male |
| P2RFC-2371-39 | P2RFC-2371-78 | 4.3-10 Male | N Male Right Angle |
| P2RFC-2375-39 | P2RFC-2375-78 | 4.3-10 Male | 7-16 DIN Male Right Angle |
| P2RFC-2317-39 | P2RFC-2317-78 | 7-16 DIN Male | 4.1-9.5 (Mini) DIN Male |
| P2RFC-2314-39 | P2RFC-2314-78 | 7-16 DIN Male | 7-16 DIN Male |
| P2RFC-2333-39 | P2RFC-2333-78 | 7-16 DIN Male | N Male |
| P2RFC-2291-39 | P2RFC-2291-78 | 7-16 DIN Male Right Angle | N Male |
| P2RFC-2319-39 | P2RFC-2319-78 | 7-16 DIN Male Right Angle | 7-16 DIN Male |
| P2RFC-2312-39 | P2RFC-2312-78 | N Male | N Male |
| P2RFC-2313-39 | P2RFC-2313-78 | N Male | 7-16 DIN Male |
| P2RFC-2315-39 | P2RFC-2315-78 | N Male | 4.1-9.5 (Mini) DIN Male |
| P2RFC-2318-39 | P2RFC-2318-78 | N Male | N Female |
| P2RFC-2339-39 | P2RFC-2339-78 | N Male | N Male Right Angle |
| P2RFC-2320-39 | P2RFC-2320-78 | N Female | 7-16 DIN Male |
| P2RFC-2345-39 | P2RFC-2345-78 | QMA Male | QMA Male |
| P2RFC-2347-39 | P2RFC-2347-78 | QMA Male | 7-16 DIN Male |
| P2RFC-2348-39 | P2RFC-2348-78 | QMA Male | N Male |
| P2RFC-2346-39 | P2RFC-2346-78 | QMA Male | N Male Right Angle |
| P2RFC-2369-39 | P2RFC-2369-78 | QMA Male | 4.3-10 Male |
| P2RFC-2377-39 | P2RFC-2377-78 | QMA Male | 4.1-9.5 (Mini) DIN Male |

*Specifications subject to change without notice. SPP-250 is a registered trademark of Times Microwave Systems.