

Low PIM .141" Conformable Semi-Rigid Cable Assemblies

- Low PIM: $\leq -155\text{dBc}$ N assemblies
 $\leq -140\text{dBc}$ QMA assemblies
- Operating Frequency: up to 3,000 MHz
- VSWR: $\leq 1.20:1$ up to 2,400 MHz
- Available in custom lengths



Low PIM 1/2" Super Flexible Corrugated Cable Assemblies

- Low PIM: $\leq -155\text{dBc}$
- Operating Frequency: up to 3000 MHz
- VSWR: $\leq 1.10:1$ up to 2,400 MHz
 $\leq 1.15:1$ up to 3,000 MHz
- Helical copper tube construction
- Available in custom lengths



Low PIM 1/2" Flexible Corrugated Cable Assemblies

- Low PIM: $\leq -155\text{dBc}$
- Operating Frequency: up to 3000 MHz
- VSWR: $\leq 1.10:1$ up to 2,400 MHz
 $\leq 1.15:1$ up to 3,000 MHz
- Corrugated copper tube construction
- Available in custom lengths



100% PIM Tested to Assure Performance

Low PIM Conformable Semi-Rigid .141"	
Description	Number
N Male to N Male; DC-3 GHz, conformable semi-rigid .141", 3 foot	P2RFC-2000-36
N Male to N Male; DC-3 GHz, conformable semi-rigid .141", 6 foot	P2RFC-2000-72
N Male to N Male; DC-3 GHz, conformable semi-rigid .141", 9 foot	P2RFC-2000-108
N Male to QMA Male; conformable semi-rigid .141", custom length	P2RFC-2102-XX

XX = custom length

Low PIM 1/2" Super Flexible Corrugated	
Description	Number
7/16 DIN Male to 7/16 DIN Male; 1/2" Super Flexible Cable, 3 foot	P2RFC-2007-36
7/16 DIN Male to 7/16 DIN Male; 1/2" Super Flexible Cable, 6 foot	P2RFC-2007-72
7/16 DIN Male to 7/16 DIN Male; 1/2" Super Flexible Cable, 9 foot	P2RFC-2007-108
N Male to N Male; 1/2" Super Flexible Cable, 3 foot	P2RFC-2008-36
N Male to N Male; 1/2" Super Flexible Cable, 6 foot	P2RFC-2008-72
N Male to N Male; 1/2" Super Flexible Cable, 9 foot	P2RFC-2008-108

Low PIM 1/2" Flexible Corrugated	
Description	Number
7/16 DIN Male to 7/16 DIN Male; 1/2" Flexible Cable, 3 foot	P2RFC-2009-36
7/16 DIN Male to 7/16 DIN Male; 1/2" Flexible Cable, 6 foot	P2RFC-2009-72
7/16 DIN Male to 7/16 DIN Male; 1/2" Flexible Cable, 9 foot	P2RFC-2009-108
N Male to N Male; 1/2" Flexible Cable, 3 foot	P2RFC-2010-36
N Male to N Male; 1/2" Flexible Cable, 6 foot	P2RFC-2010-72
N Male to N Male; 1/2" Flexible Cable, 9 foot	P2RFC-2010-108