Coax Cable Assemblies

Low Loss, High Performance

Features

- **Factory terminated and tested**
- **Dual-wall adhesive heat shrink on all connectors**
- **Labeling available for part numbers, logos, instructions, etc.**
- **Cables packaged to your specifications**
- **Colored heat shrink available**
- **All cables tested for continuity; sweeping available upon request**
- **Available with Times Microwave LMR®, equivalent cable manufactured by RF Industries or customer specified cable and/or connectors**
- **Plenum and fire retardant versions available**
- **Available in custom, configurations: lengths, connectors, and other cables**

TIMES LMR® BRAND LOW LOSS CABLE
Available in custom configurations: lengths, connectors, & other cables

Description	Part Number
N Male to N Male; LMR-240	RFW-5586-XX
N Male to N Male; LMR-400	RFW-5580-XX
SMA Male to SMA Male; LMR-240	RFW-5785-XX
SMA Male to SMA Male; LMR-400	RFW-5012-XX
QMA Right Angle Male to SMA Male; LMR-240	RFW-12367-XX
QMA Right Angle Male to QMA Right Angle Male; LMR-240	RFW-12474-XX

Note: XX indicates length in inches.
LMR is a registered trademark of Times Microwave Systems.

RF INDUSTRIES BRAND LOW LOSS CABLE
Available in custom configurations: lengths and connectors

Description	Part Number
N Male to N Male; CBL-CU240	RFW-12696-XX
N Male to N Male; CBL-CU400	RFW-12602-XX
SMA Male to SMA Male; CBL-CU240	RFW-12647-XX
SMA Male to SMA Male; CBL-CU400	RFW-12718-XX
QMA Right Angle Male to SMA Male; CBL-CU240	RFW-12719-XX
QMA Right Angle Male to QMA Right Angle Male; CBL-CU240	RFW-12645-XX

Note: XX indicates length in inches.

Manufactured by

RF Cable Assembly
Division of RF Industries
(800) 233-1728
(858) 549-6340
www.rfcables.com
rfi@rfindustries.com

Assembled in the USA