

# Low PIM Coaxial Adapters

## 4.1/9.5 (Mini) DIN and Low PIM Adapter Kits

### 4.1/9.5 (Mini) DIN Adapter Features

- Low PIM:  $\leq -160$  dBc
- Operating Frequency: up to 7.5 GHz
- Low VSWR:  $\leq 1.20:1$  up to 3 GHz
- Non-magnetic
- Non-tarnish white bronze (tri-metal) plating



### Kit Features

- Adapter protection
- Die-cut foam
- Zippered leatherette case
- Stands upright for compact storage

### LOW PIM 4.1/9.5 (MINI) DIN TO 4.1/9.5 (MINI) DIN ADAPTERS



4.1/9.5 Male to 4.1/9.5 Female  
**RFD-4195-1950**



4.1/9.5 Female to 4.1/9.5 Male  
**RFD-4195-1952**



4.1/9.5 Female to 4.1/9.5 Female  
**RFD-4195-1953**

### LOW PIM 4.1/9.5 (MINI) DIN TO N ADAPTERS



4.1/9.5 Male to N Female  
**RFN-1046-4**



4.1/9.5 Male to N Male  
**RFN-1045-4**



4.1/9.5 Female to N Female  
**RFN-1047-4**



4.1/9.5 Female to N Male  
**RFN-1048-4**

### LOW PIM 4.1/9.5 (MINI) DIN TO 7/16 DIN ADAPTERS



4.1/9.5 Male to 7/16 Fem.  
**RFD-1681-4**



4.1/9.5 Male to 7/16 Male  
**RFD-1682-4**



4.1/9.5 Fem. to 7/16 Fem.  
**RFD-1683-4**



4.1/9.5 Female to 7/16 Male  
**RFD-1684-4**

## Low PIM Adapter Kits

(All adapters sold separately. See above and previous page.)	4.1/9.5 (Mini) DIN to N (6 Piece)	4.1/9.5 (Mini) DIN to 7/16 DIN (6 Piece)	4.1/9.5 (Mini) DIN to N (7 Piece)	4.1/9.5 (Mini) DIN to 7/16 DIN (7 Piece)	7/16 DIN to N (6 Piece)	7/16 DIN to N (6 Piece)
	White bronze (tri-metal) plating and stainless steel hex nuts					Silver Plated with knurling
Kit Part Number	RFA-4195-01	RFA-4195-02	RFA-4195-03	RFA-4195-04	P2RFA-4013-SS	RFA-4013
In-Series Adapters	4.1/9.5 Male to 4.1/9.5 Female	4.1/9.5 Male to 4.1/9.5 Female	4.1/9.5 Male to 4.1/9.5 Female	4.1/9.5 Male to 4.1/9.5 Female	7/16 Female to 7/16 Female barrel	7/16 Female to 7/16 Female barrel
	4.1/9.5 Male to 4.1/9.5 Female Right Angle	4.1/9.5 Male to 4.1/9.5 Female Right Angle	4.1/9.5 Male to 4.1/9.5 Female Right Angle	4.1/9.5 Male to 4.1/9.5 Female Right Angle	7/16 Male to 7/16 Female, Right Angle	7/16 Male to 7/16 Female, Right Angle
	na	na	4.1/9.5 Female to 4.1/9.5 Female	4.1/9.5 Female to 4.1/9.5 Female	na	na
Between-Series Adapters	4.1/9.5 Male to N Female	4.1/9.5 Male to 7/16 Female	4.1/9.5 Male to N Female	4.1/9.5 Male to 7/16 Female	7/16 Male to N Female	7/16 Male to N Female
	4.1/9.5 Male to N Male	4.1/9.5 Male to 7/16 Male	4.1/9.5 Male to N Male	4.1/9.5 Male to 7/16 Male	7/16 Male to N Male	7/16 Male to N Male
	4.1/9.5 Female to N Female	4.1/9.5 Female to 7/16 Female	4.1/9.5 Female to N Female	4.1/9.5 Female to 7/16 Female	7/16 Female to N Female	7/16 Female to N Female
	4.1/9.5 Female to N Male	4.1/9.5 Female to 7/16 Male	4.1/9.5 Female to N Male	4.1/9.5 Female to 7/16 Male	7/16 Female to N Male	7/16 Female to N Male

