

Power Tapper 4.3-10 Type

Frequency 350-2700MHz

Features

Low Insertion Loss

Low VSWR

Low PIM -155dBc

200 Watt Average Power

RoHS Compliant


Install Bracket Included



GENERAL SPECIFICATIONS

Frequency Range.....	350-2700MHz
Impedance.....	50Ω
Power Rating.....	200W avg
PIM, Passive IM.....	≤-155dBc@2x43dBm
IP Grade.....	IP65
Temperature Range.....	-35° C to +85° C
Connector Type.....	4.3-10 Female
Housing Material.....	Aluminum
Color.....	Black

Electrical Specifications					
Model Number	Coupling	Branch Flatness ref. to Input Level, incl Loss, dB		Input VSWR max	
		340-960	1710-2700	340-960	1710-2700
RFPT-43F-A3	3.0dB	±1.2	±0.5	1.30:1	1.25:1
RFPT-43F-A48	4.8dB	±1.2	±0.5	1.30:1	1.25:1
RFPT-43F-A6	6.0dB	±1.2	±0.5	1.30:1	1.25:1
RFPT-43F-A7	7.0dB	±1.0	±0.5	1.30:1	1.25:1
RFPT-43F-A10	10.0dB	±1.0	±0.5	1.25:1	1.25:1
RFPT-43F-A20	20dB	±1.2	±0.6	1.25:1	1.25:1



MOUNTING BRACKET INCLUDED

